

1890 Swarthmore Avenue, PO Box 2020, Lakewood, NJ 08701 Phone: 800-526-3694, 732-363-4700, Fax: 732-364-8110 www.encoreplumbing.com • www.componenthardware.com

PROJECT NAME:	
LOCATION:	
SPECIFIER ITEM NO	QTY:
ENCORE PART NO.	

Encore® Deck Mount 4" (102mm) Centerset Faucet with Cast Spout and Wrist Blade Handles


# KL83-4x04-CEx Series

KL83-4004-CE4 4" Handles, Compression Valves

KL83-4104-CE4 4" Handles, Ceramic Valves

KL83-4004-CE6 6" Handles, Compression Valves

KL83-4104-CE6 6" Handles, Ceramic Valves



Dimensions shown in inches (mm) are for reference only and are subject to change.

1-1/8" (29mm) holes for deck are recommended to accommodate 1/2" supply nipples 1/2" NPSM Male Inlets with Compression Fittings Operating Temperature: 40-180°F (5-83°C) Operating Pressure: 15-125psi

Approximate shipping weight - 5 lbs Warranty - 2 years parts

Solid heavy duty cast body is specification and commercial quality

### **Commercial Quality Features**

- Polished chrome plated cast brass body
- 4" (102mm) cast spout
- ADA-compliant 4" (102mm) wrist blade handles
- · Built-in check valves to prevent cross-flow and back-flow

#### SANIGUARD® Product Protection

- · Permanently incorporated on all touch points of Encore plumbing fixtures
- Inorganic, silver ion technology inhibits growth of common bacteria, yeasts, mold and fungi, minimizes cross-contamination

#### **SPECIFICATIONS:**

Deck Mount Centerset Faucet to be Encore KL83 Series in the following configuration:

\_\_\_\_ KL83-4004-CE4 4" Handles, Compression Valves KL83-4104-CE4 4" Handles, Ceramic Valves

KL83-4004-CE6 6" Handles, Compression Valves

KL83-4104-CE6 6" Handles, Ceramic Valves

Faucet body to be constructed of polished chrome plated brass with total lead content less than 0.25% by weighted average. Wrist blade handles to be incorporated with SANIGUARD treatment. Valves to be 1/4-turn with integral check valve to prevent cross-flow and back-flow. Color coded temperature indexes shall meet international standards. Spout to be 4" (102mm) cast. 2.2gpm aerator @60psi standard with full flow stream bubbler screenspout tip.

For a complete list of available options for KL83-4004-C Series, see product configurator on reverse.

COMPLIES WITH:

ASME A112.18.1-2005
CSA B125.1-05
NSF/ANSI 61/9, ANNEX G
SECTION 116875 OF THE
CALIFORNIA HEALTH & SAFETY CODE
(COMMONLY KNOW AS AB1953)
VERMONT ACT 193
UNIFORM PLUMBING CODE











www.encoreplumbing.com • www.componenthardware.com

## Faucet Configuration for KL83-4004-C Series

