

"Your Solutions Partner"

Specifications

F.O.B. Sedalia, Missouri 65301



OPTIONS:

- ☐ 14 gauge tops
- ☐ Tray slides TS3BTS-HD/FX, TSSOLID-HD/FX
- □ Electric outlets TE-OP1, TE-OP2, TE-OP3, TE-OP4
- 6', 8' or 10' cord and plug
- Pusher bar TMOD-7
- □ Bumpers TMOD-8
- ☐ Stainless steel legs TMOD-15
- Stainless steel drawer with or without lock & keys
- Veneered plastic laminate panels on body TSS-xP
- Powder coat paint colors
- Grommeted top cutout
- Interior shelf
- Stainless steel kickplates

DUKE MANUFACTURING CO. 2305 N. Broadway St. Louis, MO 63102

800.735.3853 Toll Free 314.231.1130 In Missouri 314.231.5074 Fax www.dukemfg.com

Approval Stamp(s):									
PRO	JECT INFORMATION:								
PR	OJECT:								
ITE	100000								
QU	ANTITY:								
MOI	DEL:								
	urmaduke Serving S ishier Stand	Syst	tems						
ū	TCS-30								
TOP	*								
:	16 gauge, 300 Series stainless stee Sound-deadening vinyl foam tape t Internal locking devices		en lop and body						
BOD	Y:								
	Choice of (12) powder coat paint of #217105 - Bright White #217150 - Orange #217107 - Hollyberry Red #217127 - Fence Green #217102 - Silver Hammer #217101 - Semi-Gloss Black Stainless steel body NSF listed, 5" diameter polyurethar Operator's side open to foot rest End panels die-formed into channe Ends and side opposite operator fu	ne cas	#217103 - Natural Almond #217154 - Racing Red #217120 - Sky Blue #217152 - Stone Gray #217113 - Brown Kickplate #217125 - Textured Black						


SHORT FORM SPECIFICATIONS:


Duke Thurmaduke Serving Systems - Cashier Unit. Top shall be constructed of 16 gauge, 300 Series stainless steel with edges flanged down 2" at 90° on all four sides and flush with body on ends. Vinyl foam tape to be used between top and body for sound-deadening. Body of unit shall be free standing and formed of heavy gauge, powder coat painted steel with specified color or 300 Series stainless steel. Operator's side of unit shall be open to foot rest with corners of end panels die-formed into channels. Side opposite operator and ends are fully enclosed. Opening shall allow knee room and is provided with stainless steel tubular foot rest. Unit to be mounted on NSF approved 5" polyurethane casters, all swivel, two with locks. Must add "PG" to model number for Paint Grip Bodies; "SS" for Stainless Steel Bodies.



□ TCS-30







RIGHT SIDE VIEW

DIMENSIONS:

Freight Class: 100

Model	Length		Width		Height		Cube ft.	Weight		Drawer Size					
										Length		Width		Depth	
	in.	cm	in.	cm	in.	cm	crated	lbs.	kg	in.	cm	in.	cm	in.	cm
TCS-30	30	76.2	32	81.3	36	91.4	33.0	242	110.0	24-3/8	62.0	20	50.8	3-1/2	8.9

INSTALLATION DATA:

Must specify location of drawer

Power Supply:

n/a



DUKE MANUFACTURING CO. 2305 N. Broadway St. Louis, MO 63102

800.735.3853 Toll Free 314.231.1130 In Missouri 314.231.5074 Fax www.dukemfg.com

07/04