



Item # _____

Job _____



Metro C5 4 Series Insulation Armour™ Plus Heated Holding Cabinets

Metro C5 4 Series Insulation Armour™ Plus Heated Holding Cabinets

- **Insulation Armour™ Plus:** Patented insulation technology replaces traditional sheet metal exterior with foamed-in-place polyurethane polymer panels, providing improved energy efficiency at a lower initial investment. Armour panels have molded in handles and act as a full body bumper for improved handling and protection in mobile applications.
- **Stainless Steel Construction:** High quality, Type 304 stainless steel for easy cleaning and long-term durability.
- **Top-Mounted Controls:** Ergonomic user-friendly controls are mounted at the top of the cabinet for improved access and readability, to prevent damage, and easy cleaning.
- **Performance:** Forced convection design gently circulates hot air for improved temperature consistency. Heat is channeled to the bottom of the cabinet, allowing it to rise naturally without it blowing directly over the food. Thermostatically controlled, 200°F (93°C) maximum operating temperature.
- **Slide Configurations:** Two slide styles provide maximum holding capacity. Universal slides hold 12" x 20" steam pans, 18" x 26" sheet pans, and GN pans are adjustable on 1½" increments. Lip load slides exclusively hold 18" x 26" sheet pans on 1½" fixed increments.
- **Reliability:** Reliability and durability are designed from the ground up. High-quality components provide a long life of worry free use.



InterMetro Industries Corporation
North Washington Street
Wilkes-Barre, PA 18705
www.metro.com



13-94



C5 4 Series Insulation Armour™ Plus Heated Holding Cabinets

Specifications

- **Dimensions:** 69¹/₂" H x 30" W x 33" D (1766mm x 762mm x 839mm)
- **Cabinet Material:** Type 304 stainless steel, 20-gauge cabinet body with High Density Polyethylene (HDPE) exterior
- **Insulation:** Insulation Armour™ Plus HDPE polymer panels with 2" thick CFC free foamed-in-place polyurethane insulation. High-density fiberglass insulation on top (3" thick) and bottom (1¹/₂" thick).
- **Casters:** 5" (127mm) diameter donut neoprene wheel. Plate mounted, 2 swivel and 2 swivel with brake.
- **Door:** Type 304 stainless steel, 20-gauge insulated, welded door. Field reversible, 180° swing. Fully insulated with 2" thick high density fiberglass insulation.
- **Door Latch:** Chrome plated, high-strength flush-mounted magnetic latch with lever-action release.
- **Door Gasket:** High temperature, door mounted, Santoprene gasket.
- **Door Hinges:** Type 304 stainless steel, 11-gauge heavy-duty pivot hinge with welded pin.
- **Universal Wire Slides:** 1/4" (6.4mm) diameter nickel-chrome electroplated wire, adjustable on 1¹/₂" (38mm) increments. Type 304 stainless steel vertical standards.
- **Lip Load Slides:** 1¹/₂" x 1/2" x 0.063" (38mm x 13mm x 1.6mm) extruded aluminum channel slides, fixed on 1¹/₂" spacing, riveted to .063" aluminum vertical standards.
- **Heat Generation System:** Thermostatically controlled 1360W heating element, ball bearing blower motor, and ducted air system.
- **Cord:** 7¹/₂' power cord with right angle NEMA 5-15P plug end. Factory mounted on top, can be easily field reversed to rear.
- **Clearance Requirements:** 18" (458mm) away from any cooking equipment. AVOID contact with any surfaces that exceed 200°F (93°C). Recommended minimum clearance from enclosures is 1¹/₂" (38mm) on sides and rear, 6" (152mm) on top. Minimum 1/2" (13mm) clearance above under counter units is required.
- **Slide Capacities:**

Cabinet Size	Universal Wire Slide Pan Capacity											Lip Load Slide Pan Capacity	
	Slide Pairs		Sheet Pans	Steam Pans			Gastronorm				Sheet Pans		
	Provided	Max	18"x26"	12"x20"x2.5"	12"x20"x4"	12"x20"x6"	65mm Depth		100mm Depth		150mm Depth	18"x26"	
Full Height (Full Length Door)	17	34*	17**	34	22	14	2/1	1/1	2/1	1/1	2/1	1/1	34***

*Maximum number of slide pairs @1.5" spacing. Additional slide pairs ordered separately.
 **Standard capacity @ 3" spacing. Increased capacity requires additional slide pairs.
 ***Standard capacity @ 1.5" spacing.

Universal Slide Model Number

120V, 11.7A, 60Hz, 1400W

C5 4 9 - A S F S - U



NEMA 5-15P

Lip Load Slide Model Number

120V, 11.7A, 60Hz, 1400W

C5 4 9 - A S F S - L



NEMA 5-15P

Models with Accessories or Options

C5 4 9 - A S F S - U A

C5 4 9 - A S F S - L A

An "A" suffix indicates that accessories need to be factory assembled to the cabinet. Order accessories separately.

Options/Accessories:

- Travel Latch/Hasp (C54-TRVL)
- Factory Left Hand Hinging (DD3768)
- 6" Casters (C5-6CASTER)
- Rear Rigid Casters (C5-RDGCSTR)
- 6" Stainless Steel Legs (C5-SSLEGS)
- Straight Plug, 120V (C5-STRPLG-15)
- Twist Lock Plug, 120V (C5-RTWSTPLG-15)
- Small Item Shelf (C5-SHELF-S)
- Universal Slide Pair, Chrome (C5-USLIDEPR-C)
- Universal Slide Pair, Stainless (C5-USLIDEPR-S)
- Stainless Steel Universal Slides (C5-USLIDE-9S)

All Metro Catalog Sheets are available on our website: www.metro.com



InterMetro Industries Corporation

North Washington Street, Wilkes-Barre, PA 18705

Phone: 570-825-2741

Product Information. U.S. and Canada: 1.800.992.1776

Outside U.S. and Canada: www.metro.com/contactus

L02-194

Printed in U.S.A. 2/15

Information and specifications are subject to change without notice. Please confirm at time of order

Copyright © 2015 InterMetro Industries Corp.